

Technical Field and Background of the Invention
"Delivery Box"

Int B1 ~~This invention relates to a delivery box for goods~~

including groceries ordered by Internet, mail or otherwise;

~~for mail; and for other articles.~~

Summary of the Invention

- a*
- 5 The object of the invention is to enable articles to be delivered at any time of day or night to a building whether occupied or not, and to be kept safely until retrieved by the occupier.

~~The invention comprises a delivery box adapted to be~~
10 secured to a fixed support and having an outer door which is openable to enable deliveries to be placed inside the box but which locks automatically when it is then closed.

Preferably, the support is a wall of a building.

The box may be bolted internally to the exterior
15 surface of the wall.

Alternatively, the box is built into the wall. The built-in box may have a rear door openable directly into, and lockable from, the interior of the building.

Int B2 ~~The outer door of the built-in box is preferably~~
20 substantially flush with the exterior surface of the wall.

The outer door may have a letter deposit flap.

The flap may open into a receptacle mounted on the back of said door.

Int B3 ~~The outer door may have a bank-type deposit drawer.~~

Int B4 ~~The box is preferably adapted to be supplied with~~
25 mains electricity.

Int B5 ~~The box may be a chilled storage compartment.~~

FOI240-1244850

The box may include a frozen storage compartment.

~~The outer door may have a digital computerised locking system operable by pre-arranged single-use code numbers.~~

The box may be adapted to be connected to an existing
5 alarm system.

The box may have an external child-resistant grille
with an opening catch at a high level.

ABD Brief Description of the Drawings
The invention will now be described in greater detail,
by way of example only, with reference to the accompanying
10 diagrammatic drawings, of which:-

Figure 1 is a front elevation of one form of a large delivery box particularly suitable for accepting deliveries of articles of food;

Figure 2 is a sectional side elevation of said one
15 form of large box built into an external wall of the house;

Figure 3 is a front elevation of one form of smaller delivery box;

Figure 3a is a sectional side elevation of said one form of smaller box built into an external wall of the
20 house;

Figure 4 is a front elevation of another form of smaller delivery box;

Figure 4a is a sectional side elevation of said other form of smaller box built into an external wall of the
25 house;

Figure 5 is a front elevation of another form of large delivery box; and

T04240" T224T4850

213
B7 Description of Preferred Embodiment and Best Mode
~~Referring now to Figures 1 and 2 of the drawing~~

[illegible]

B7C

~~pre-arranged single-use code number which is erased from~~
the system's memory when said door is closed and self-
locked. The box 10 is adapted to be connected to a burglar
alarm system (not shown) existing within the house. A
5 typical size for a large box 10 suitable for accepting,
inter alia, deliveries of food from a supermarket is, say,
1200 millimetres in internal height by 600 millimetres in
internal width and depth, but a height of more than two
metres is preferably avoided as this would require planning
10 permission. It will be understood that the delivery box 10
just described is a de luxe or top of the range unit. Many
of its features can be omitted without departing from the
scope of the invention, and a less sophisticated locking
system for the outer door 20 such as a high-security Yale-
15 type lock can be employed, in which case said door is left
unlocked until a delivery has been made. The external
child-resistant grille (not shown) with an opening catch
disposed at a high level so as to be difficult for a child
to reach then becomes a desirable adjunct to the box 10.

T04240" F24T4860

20 38 | ~~Referring now to Figures 3 and 3a of the drawings, a~~
smaller delivery box indicated generally at 40 which is
still large enough to accept supermarket and mail order
deliveries is built into an external masonry wall 41 of a
house. The box 40 has only an outer door 42 with a handle
25 44 and hinges 46, which is openable to enable deliveries to
be placed inside said box but which locks automatically
when it is closed. The locking system employed can be

BS
 either of the digital computerised type or of the high-
 security Yale-type hereinbefore referred to, and an
 external grille as described in the preceding paragraph can
 be fitted if desired. The door 42 of the box 40 is fitted
 5 with a large letter deposit flap 48 which conveniently
~~opens into a receptacle 49 mounted on the back of said~~
~~door.~~

Figures 4 and 4a of the drawings show a delivery box
 indicated generally at 50 which is in most respects similar
 10 to the box 40 shown in Figure 3 but which has fitted in its
 outer and only door 52, instead of a letter deposit flap, a
 bank-type deposit drawer 54.

A typical size for the boxes 40 and 50 is, say, 900
 millimetres in internal height by 600 millimetres in
 15 internal width and depth.

BS
~~Figures 5 and 5a of the drawings show a large delivery~~
 box having an outer and only door 62 with a handle 64 and
 hinges 65 which is secured to the external surface of an
 exterior wall 66 of a house and to a concrete path 68
 20 adjoining said wall by means of internal and thus
 inaccessible masonry bolts 70. A typical size for the box
 60 is, say, 1500 millimetres in height by 600 millimetres
 in internal width and depth. The door 62 is openable to
 enable deliveries to be placed inside said box but locks
 25 automatically when it is closed, the locking system being
 either of the digital computerised type or of the high-
~~security Yale-type hereinbefore referred to.~~

FOI 240-1244860

In a modification, the box can be secured to other fixed supports such as a concrete base or a post.

Thus there are provided secured delivery boxes which save time and money by avoiding any need for redelivery.

09841421 042401
FOI240 T24T4860